

## NINGBO RUYI JOINT STOCK CO., LTD

Billy Ying Zhejiang, China E. billyying@xilin.com, Ph. +86-574-65552011  
 Ben Chu Zhejiang, China E. ben@xilin.com, Ph. +86-574-65552011  
 Michille Shi Zhejiang, China E. michille@xilin.com, Ph. +86-574-65552011



### Xilin CPD20SR18

China

*onQ-32578*

FORKLIFTS - COUNTER BALANCE ELECTRIC  
 NEW - SALE

<b>Date Listed</b>	28 Apr 2023
<b>Reference</b>	CPD20SR-18
<b>Power Type</b>	Battery Electric
<b>Lift Capacity</b>	1,800 kg(3,968 lb)
<b>Mast Type</b>	Triplex (3 Stage)
<b>Maximum Lift Height</b>	6,000 mm(236 in)
<b>Tyre Type</b>	Solid / Puncture Proof
<b>Machine Height (Mast Lowered)</b>	2,595 mm(102 in)
<b>Machine Features</b>	Mast full free lift Overhead Guard Charger

#### ADDITIONAL INFORMATION

**SAFETY AND STABILITY** • This feature appears especially important when in or out of the container, and carrying goods in congested area and narrow aisle. Standing type design with wide view clear visibility. • Imported drive wheel and mast. • With multi-function LED display with BID can be programmed, include battery discharge faulty code, drive direction, hour meter, brake situation etc. • Advanced AC control system offers strong driven ability. No brush with generative brake. • Offers three type driven speed: low speed, normal speed, high speed. You may choice according to different request. • Multi-function type joy stick can control forward, reverse, mast lifting/lowering tiling and sideshift etc. easy to operate. • Germany made magnetic multi-valve, with proportional valve and offers adjustable lifting/lowering speed • Wet disc brake. • With small turning radius 1440mm and aisle width smallest is 3060mm.

**OFFERS 6 TYPE CONTROL SPEED** • System Controlled Hydraulic Speeds: The hydraulic system automatically controls tilt and stable side-shift speed to increase forklift stability and operator confidence. • Travel Speed Control: truck can automatically controls travel speeds and braking based on fork height and other operating conditions. • Cornering Speed Control: the truck will automatically adjust travel speed when steering. • Ramp Speed Control: The intelligent control system can maintains holds truck stopped on the ramp until the operator start travel forward at a constant speed. • Safe Speed Control: The forklift will slow down automatically if the foot of the operator places out of the standing platform. • Lift/lower Speed Control The operator can adjust the lift and lower speed by control handle. **ERGONOMICS** • With adjustable armrest, comfortable and stable. Suit for different height driver using. • Large compartment for standing, with foot relax plate, can effectively relax foot while static operation. • The standing platform has a good shock absorption, conform to ergonomic design to make the operation more comfortable. • The adjustable armrest and seat provides padded support to ensure the hand comfortable and stable, and meet different requirements for the operators. **SERVICE ABILITY** • Easy reach to electrical system while open the front cover, easy for maintenance. • Driving motor and lifting motor are all with AC system, brushless easy to maintain external encoder is easy to replace. • Sideway moving battery with lock system it is convenience for maintenance. • Lifting function will be cutoff while battery

discharge is over 80%. • The multi-function display with error code can easy to check troubles of truck.

## BETTER, SMARTER, MORE FOCUSED, EASY AS.

- Machinery-onQ Asia is a platform for the sale and acquisition of both new & used mobile machinery in the Middle East, South, East and Southeast Asia.
- The platform features forklifts, warehouse equipment, container handlers, log handlers, aerial work platforms, port cranes, tow trucks, terminal tractors, industrial sweepers and forklift attachments.

This platform is produced by FORKLIFTACTION



Machinery-onQ is a Business Platform by ForkliftAction Media.

<https://asia.machinery-onq.com/machine-forklifts-counter-balance-electric-xilin-cpd20sr18-new-sale-china/32578>

© ForkliftAction Media 2025