



Xilin FB35

China

onQ-32579

FORKLIFTS - COUNTER BALANCE ELECTRIC
NEW - SALE

Date Listed	28 Apr 2023
Reference	FB35
Power Type	Battery Electric
Lift Capacity	3,500 kg(7,716 lb)
Mast Type	Triples (3 Stage)
Maximum Lift Height	7,000 mm(276 in)
Tyre Type	Solid / Puncture Proof
Machine Height (Mast Lowered)	2,045 mm(81 in)
Machine Features	Mast full free lift Overhead Guard 4 wheels Front wheel drive Charger Side shift

ADDITIONAL INFORMATION

High stability and safety • Cab design by SIP point , conform to EN-ISO 5353, ensures compartment with great comfort and fatigue- free operating. • Multifunction LCD digital display with digital service hour metre, battery discharge indicator, travel records, error code and warning displays. Provide fast and accurate monitoring truck status. • Mast cylinder lowering with buffering system: shock absorber steering axle with low noise. All of seal kits imported from Japan (NOK), transmission and working system have low noise. • With regenerative brake in reversing mode and regular brake pedal use, truck can be braked after foot leaving the pedal. reduce operator efforts and improve the brake life. • The optional of third safety pedal to reduce the driving speed while stacking and steering application. Ergonomics • Wide view mast, clear visibility. • Low height access step with wide steel non slip plate for easy entry and exit. • Cowl-mounted hydraulic levers design offers big operation space. • Adjustable tilt steering column offers the most comfortable operator position. • Seat with safety belt and arm rest (The optional of Grammar or suspension type). • High-friction brake shoes are free of asbestos. • With reverse mirror, front work light and back work light group. Easy maintenance • Floor board are easily removed for quick service assess. • Insulated battery cover gas-filled cylinders and easy to maintain. • The lifting motor under the floorboard for easy maintenance.