

**Wellwit
WMF1000**

Shenzhen, Guangdong, China

onQ-65285

WAREHOUSE MOVERS & LIFTS - REACH TRUCKS & STACKERS
NEW - SALE

Date Listed	29 Oct 2024
Reference	WMF1000
Power Type	Battery Electric
Lift Capacity	1,400 kg(3,086 lb)
Mast Type	Simplex (1 Stage)
Maximum Lift Height	3,000 mm(118 in)
Tyre Type	Polyurethane / Vulkollan
Machine Height (Mast Lowered)	2,040 mm(80 in)
Machine Features	Load backrest Multi directional / 4-way

ADDITIONAL INFORMATION

Operation: Telecontrol/Laser navigation Load center: 600mm Axle centre to fork face: 648mm Wheel base(fork raised/lowered): 877mm Fork lowering minimum height: 104mm Axle load with load, drive/load side: 730/1350kg Axle load without load drive /load side: 450/230kg Tyre, operator/load side: Rubber(R),polyurethane(pu): Polyurethane Tyre size ,driving side: $\Phi 230 \times 75$ mm Tyre size, load size: $\Phi 80 \times 54$ mm Tyre size, balancing side: $\Phi 115 \times 55$ mm Wheels number ,drive /load side (x=driven): 1x-2/4 Track width, drive side b10: 390/500mm Track width ,load side b11: 538mm Height of mast , extended h4: 2130mm Fork height , lowered h5: 85mm Navigation height h6: 2000mm Charging port center height h7: 500mm Overall length L1: 1565mm Length to fork face L2: 426mm Charging port center distance, front end of shelving L3: 180mm Overall width b1: 882mm Fork size(length/width/height) l/e/s: 1150/180/55mm Width of fork (outside b3: 560/680(note1) Minimum ground clearance m1: 30mm Aisle width, 1000x1200mm pallet crosswise Ast : 1885mm Aisle width 800x1200mm pallet lengthwise Ast: 1685mm Minimum turning radius Wa: 1130mm Travel speed , with/without load: 5/6km/h Lift speed, with/without load: 115/170mm/s Lower speed ,with/without load: 160/125mm/s Travel speed , with/without load: 5/6km/h Lift speed, with/without load: 115/170mm/s Lower speed ,with/without load: 160/125mm/s Climbing ability(S2,5min) , with/without load,5min.rating: 3/5% Drive motor output(S2,60min): 1.25kw Lift motor output(S3,10%) : 3kw Turning motor output(S2,10min): 0.165kw Battery type: Lithium iron phosphate battery Battery voltage/rated capacity(5h): 24v/180Ah Battery weight: 58kg Type of drive control: AC motor speed feedback Noise that the driver heard according to EN12053: ≤ 70 dB(A)

